In the Claims

Please amend the Claims as follows:

- 1. (Currently Amended) In combination with one or more graft segments configured to operably transport bypass blood flow from a singular supply location to one or more delivery locations in a grafted network, means an apparatus for directing such bypass blood flow in said grafted network to one or more vascular members, said means apparatus comprising:
- multiple channel blood flow connector and second graft segments to coupling first a first vascular member comprising a first blood flow delivery location, said flow connector including a supply conduit and a delivery conduit integrally formed therewith and adjacently disposed with respect to one another, with said supply conduit and said delivery conduit each having distinct lumen formed therewithin, said supply conduit having first and second opposed open ends having coupling means for operably attaching each being operably coupled to respective first open ends of such first and second graft segments thereto, said supply lumen and said delivery lumen being fluidly connected to one another through cooperating apertures in respective outer walls of said supply conduit and said delivery conduit at an intersection therebetween so as to provide for immediate bypass blood flow from said supply lumen to said delivery lumen, said delivery conduit having at least one a first open end portion extending from said intersection and beyond an outer circumferential dimension a first perpendicular tangential plane of said supply conduit outer wall at a lateral side thereof with respect to said intersection, such that a first open end of

said delivery conduit is laterally spaced from said supply conduit outer wall, said delivery conduit being configured for operable implantation directly into the first vascular member so as to provide bypass blood flow thereto, said delivery conduit being specifically sized to provide internal structural support for the first vascular member when said delivery conduit is implanted therein; and

a flow restricting means operably coupled to a second open end of said second graft segment, and being operably disposed within the grafted network adjacent a terminal delivery location.

- 2. (Currently Amended) A means An apparatus as in Claim 1 wherein said first and second open ends end of said supply conduit are is tapered such that the thickness of said supply conduit outer wall at said first and second open ends end is less than about 50% of the thickness of said supply conduit outer wall at locations between said first and second open ends end and said intersection.
- 3. (Currently Amended) A means An apparatus as in Claim 1 wherein at least said first open end of said delivery conduit is tapered such that the thickness of a delivery conduit outer wall at said first open end is less than about 50% of the thickness of said delivery conduit outer wall at locations between said first open end and said intersection.
 - 4. (Cancelled)
- 5. (Currently Amended) A means An apparatus as in Claim 1 wherein said cooperating apertures have radiused edges.
- 6. (Currently Amended) A means An apparatus as in Claim 1 wherein inner surfaces of said supply conduit and

said delivery conduit are polished to a surface smoothness of about 26 μ inches.

- 7. (Currently Amended) A-means An apparatus as in Claim 1 wherein the first graft segment is operably coupled to the blood flow supply location and said first open end of said supply conduit of said flow connector, and a first end of the second graft segment is operably coupled to said second open end of said supply conduit of said flow connector.
 - 8. (Cancelled)
- 9. (Currently Amended) A means An apparatus as in Claim 8 1 wherein said flow restricting means includes first and second open ends operably coupled to respective graft segments in said grafted network, with one of said respective graft segments extending between said flow restricting means and said terminal delivery location.
- 10. (Currently Amended) A means An apparatus as in Claim 9 wherein said blood flow supply location is an aorta, and said terminal blood flow delivery location is an atrium or vena cava of a patient.
- 11. (Currently Amended) A means An apparatus as in Claim 1, including one or more biocompatible coatings on at least inner surfaces of said flow connector.

- 12. (Currently Amended) A means An apparatus as in Claim \$ 1, including one or more biocompatible coatings disposed on at least inner surfaces of said flow restricting means.
- 13. (Currently Amended) A means An apparatus as in Claim 11 wherein at least one of said biocompatible coatings comprises silane, polyvinylpyrrolidine, heparin, and a photo-reactive cross-linking agent.
- 14. (Currently Amended) A means An apparatus as in Claim 12 wherein at least one of said biocompatible coatings comprises silane, polyvinylpyrrolidine, heparin, and a photo-reactive cross-linking agent.
- 15. (Currently Amended) A means An apparatus as in Claim 1, including a biocompatible coating disposed on at least inner surfaces of selected graft segments.
- 16. (Currently Amended) A means An apparatus as in Claim 1 wherein said delivery conduit includes a second end portion having a second end, with said second end portion extending from said intersection in a direction divergent from said first end portion of said delivery conduit.
- 17. (Currently Amended) A means An apparatus as in Claim 16 wherein said first end of said delivery conduit is open, and said second end is closed.
- 18. (Currently Amended) A means An apparatus as in Claim 16 wherein said first and second ends of said delivery conduit are open.
- 19. (Currently Amended) A means An apparatus as in Claim 1 wherein said supply conduit has an external diameter of up to about 8mm and said delivery conduit has an external diameter of up to about 5mm.

- 20. (Currently Amended) A means An apparatus as in Claim 1 wherein said first end portion of said delivery conduit is at least 1mm longer than said second end portion of said delivery conduit as measured from said intersection.
- 21. (Currently Amended) A-means An apparatus as in Claim 1, including a transfer conduit interconnectably disposed between said supply conduit and said delivery conduit, said transfer conduit fluidly extending between respective said cooperating apertures in said supply conduit and said delivery conduit, said transfer conduit having first and second opposed open ends, at least one of said open ends being flared outwardly from an annular apex to an annular outer end, said annular outer end having a diameter exceeding the outer diameter of said transfer conduit by between about 0.25 and 1.5mm.
- 22. (Currently Amended) A means An apparatus as in Claim 21 wherein said transfer conduit is angled with respect to said supply conduit of said flow connector in an orientation such that an obtuse angle of at least about 100° is formed as delineated between said transfer conduit and said first open end of said supply conduit which receives blood flow from the supply location, and correspondingly an acute angle of less than about 80° is formed between said transfer conduit and said second open end of said supply conduit of said flow connector.
- 23. (Currently Amended) A means An apparatus as in Claim 1 wherein at least said delivery conduit is formed from a selectively expansive material for providing an interference fit between said delivery conduit and the vascular members sufficient to assist in forming a liquid-tight seal therebetween.